









# STONE REVOLUTION MATTE

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 <b>Water absorption of the body</b>	ISO 10545-3	≤ 0.5%	Conformity
 <b>Breaking strength</b>	ISO 10545-4	≥ 35N/MM <sup>2</sup>	Conformity
 <b>Abrasion resistance</b>	ISO 10545-7		PEI 5-Limestone PEI 4-Other Colors
 <b>Frost resistance</b>	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 <b>Chemical resistance</b>	ISO 10545-13	No samples must show visible sign of chemical attack	Conformity
 <b>Thermal shock resistance</b>	ISO 10545-5	≤ 1300 N min	Conformity
 <b>Dynamic coefficient of friction</b>	BOT 3000E	ANSI A137.1:2017	DCOF ≥ 0.42
 <b>Slight Variation</b>	See Below		V3



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

**BOTTEGA**  
*ceramica e stife*

[www.bfceramics.com](http://www.bfceramics.com)