









QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 <b>Water absorption of the body</b>	UNI EN ISO 10545-3	≤ 0.5%	Conformity
 <b>Breaking strength</b>	UNI EN ISO 10545-4	≥ 35 N/mm <sup>2</sup>	Conformity
 <b>Abrasion resistance</b>	UNI EN ISO 10545-7		PEI 4-White/Grey Field PEI 3-Black Field PEI 4-Decos
 <b>Frost resistance</b>	UNI EN ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 <b>Chemical resistance</b>	UNI EN ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 <b>Thermal shock resistance</b>	UNI EN ISO 10545-5		Conformity
 <b>Dynamic coefficient of friction</b>	BOT 3000E	ANSI A137.1:2012	DCOF ≥ 0.42
 <b>Slight Variation</b>	See Below		V2-All Colors Field Decos-N/A



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED



[www.bfceramics.com](http://www.bfceramics.com)