









| QUALITY CHARACTERISTICS   | NORM            | STANDARDS                          | RESULT  |
|---|-----------------|------------------------------------|---|
|  <b>Water absorption of the body</b>     | ISO<br>10545-3  | ≤ 0.5%                             | < 0.1%  |
|  <b>Breaking strength</b>                | ISO<br>10545-4  | ≥ 35 N/mm <sup>2</sup><br>≥ 1300 N | ≥ 40 N/mm <sup>2</sup><br>Conforms  |
|  <b>Abrasion resistance</b>              | ISO<br>10545-7  | ISO 10545-7                        | Class 3: Dark, Natural,<br>Flame, River<br>Class 4: Grey<br>Class 5: Gold |
|  <b>Frost resistance</b>                 | ISO<br>10545-12 | ISO 10545-12                       | Resistant   |
|  <b>Chemical resistance</b>              | ISO<br>10545-13 | Declared Value<br>Class B Minimum  | LA-HA<br>A  |
|  <b>Thermal shock resistance</b>         | ISO<br>10545-9  |                                    |   |
|  <b>Dynamic coefficient of friction</b> | BOT<br>3000E    | ANSI A137.1                        | > 0.42  |
|  <b>Slight Variation</b>               | See Below       | Substantial Variation              | V4  |



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

**CERAMICHE D'ARTE**

[www.bfceramics.com](http://www.bfceramics.com)