









# WRINKLES SEMI-POLISHED

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 <b>Water absorption of the body</b>	ISO 10545-3	≤ 0.5%	Conformity
 <b>Breaking strength</b>	ISO 10545-4	≥ 35 N/mm <sup>2</sup>	Conformity
 <b>Abrasion resistance</b>	ISO 10545-7		PEI 4 - White PEI 3 - Other Colors
 <b>Frost resistance</b>	ISO 10545-12	No samples must show ruptures or noticeable surface alterations	Conformity
 <b>Chemical resistance</b>	ISO 10545-13	No samples must show visible sign of chemical attack	Conformity
 <b>Thermal shock resistance</b>	ISO 10545-5		Conformity
 <b>Dynamic coefficient of friction</b>	BOT 3000E	N/A - Wall Tile	N/A
 <b>Slight Variation</b>	See Below		V1



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED



Everyday  
Lifestyle  
Essentials

[www.bfceramics.com](http://www.bfceramics.com)